



## SOFT ROMAN BLINDS - SPECIFICATION SHEET

<b>Headrail</b>	20mm x 40mm Pine Headboard
<b>Bottomrail</b>	50mm pocket with pine bottom bar
<b>Sides</b>	20mm taped side seams
<b>Cord Operation</b>	Swivel Cord Lock at the rear of the blind finished off with a timber acorn at the end painted to match the fabric
<b>Control Side</b>	Either Left or Right
<b>Lifter Side</b>	Either Left or Right
<b>Fabrics</b>	<b>Sunscreens, Translucent &amp; Blockouts</b>
<b>Panels</b>	Divided using Bricos easy system. Aluminium Powder coated. Only available in Black & White.
<b>Panel Sizes</b>	Drop is divided by an odd number to allow for approx 200mm for Bottom panel. The remainder of blind is double the bottom panel. The top panel of blind is approx. two and a half times the size of the bottom panel.
<b>Stacking Depth</b>	Under 1800 drop the stacking depth is 270mm To 2100 drop the stacking depth is 280mm To 2400 drop the stacking depth is 290mm
<b>Cleaning</b>	Gentle vacuum with appropriate attachment. Always exercise caution when spot cleaning. Test cleaning on non exposed surface. Avoid excessive rubbing and abrasion. Possible shrinkage – 3% pending on fabric chosen. Remove hooks, rings and trims before cleaning. Blinds are heavy when wet. Professional wet cleaning recommended.